

Flavor West Manufacturing, LLC.

Version No: 1.1.2.1 Safety Data Sheet accordtog OSHA HazCom Standard (2012) requirements Chemwatch Hazard Alert Code: 2

Issue Date: 04/30/2021 Print Date: 04/30/2021 L.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	FW-BSF N&A Bananas Foster Flavor
Synonyms	Not Available
Proper shipping name	Extracts, flavoring, liquid
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Flavor West Manufacturing, LLC.	
Address	29400 Hunco Way, Lake Elsinore CA 92530 United States	
Telephone	(951) 893-5120	
Fax	(714) 276-1621	
Website	www.FlavorWest.com	
Email	Flavor@FlavorWest.com	

Emergency phone number

Association / Organisation	Chemwatch	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	see below	+61 2 9186 1132
Other emergency telephone numbers	see below	+1 855-237-5573

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

	Flammable Liquid Category 3, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Skin Corrosion/Irritation Category 2
--	---

Label elements

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H315	Causes skin irritation.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P271	Use only outdoors or in a well-ventilated area.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

Take off contaminated clothing and wash before reuse.	
In case of fire: Use alcohol resistant foam or normal protein foam for extinction.	
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
Call a POISON CENTER or doctor/physician if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
IF ON SKIN: Wash with plenty of water.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
If skin irritation occurs: Get medical advice/attention.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
57-55-6	50-60	propylene glycol
56-81-5	20-30	glycerol
7732-18-5	1-10	water

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	Eye Contact If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasion lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. 	
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. 	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. 	

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

- Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

SECTION 5 Fire-fighting measures

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Special protective equipment and precautions for fire-fighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Moderate explosion hazard when exposed to heat or flame. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) acrolein other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. 							
	Chemical Class: alcohols and glycols For release onto land: recommended sorbents listed in order of priority.							
	SORBENT TYPE	RANK	APPLICATIC	N	COLLE	CTION	LIN	MITATIONS
	LAND SPILL	- SMAL	L					
Major Spills	cross-linked polymer - particulate		1	shovel	shovel		R, W, SS	
	cross-linked polymer - pillow		1	throw	pitchfor	k	R, DGC, RT	
	sorbent clay - particulate		2	shovel	shovel		R,I, P	
	wood fiber - pillow		3	throw	pitchfor	k	R, P, DGC, RT	
	treated wood fiber - pillow		3	throw	pitchfor	k	DGC, RT	
	foamed glass - pillow			4	throw	pichfork	(R, P, DGC, RT
	LAND SPILL - MEDIUM							
	cross-linked polymer - particulate			1	blower	skipload	ler	R,W, SS
	polypropylene - particulate			2	blower	skipload	ler	W, SS, DGC
	sorbent clay - particulate		2	blower	skipload	ler	R, I, W, P, DGC	
	polypropylene - mat			3	throw	skipload	ler	DGC, RT
	expanded mineral - particulate		3	blower	skipload	ler	R, I, W, P, DGC	
	polyurethane	e - mat		4	throw	skipload	ler	DGC, RT
	Legend DGC: Not effe R; Not reusabl I: Not incineral P: Effectivenes	le ble	C		r is dense	e		

 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. 		May be violently or explosively reactive.
--	--	---

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Consider storage under inert gas. Store in original containers in approved flammable liquid storage area. Store away from incompatible materials in a cool, dry, well-ventilated area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	 Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt.
Storage incompatibility	 Glycerol: reacts violently with strong oxidisers, acetic anhydride, alkali metal hydrides, calcium hypochlorite, calcium oxychloride, chlorine, chromic anhydride, chromium oxides, ethylene oxide, hydrogen peroxide, phosphorous triiodide, potassium chlorate, potassium permanganate, potassium peroxide, silver perchlorate, sodium hydride, sodium peroxide, sodium triiodide, sodium tetrahydroborate, is incompatible with strong acids, caustics, aliphatic amines, isocyanates, uranium fluoride is able to polymerise above 145 C Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water. Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium should not be heated above 49 deg. C. when in contact with aluminium equipment

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs)	glycerol	Glycerin (mist)- Total dust	15 mg/m3	Not Available	Not Available	Not Available

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Table Z-1						
US OSHA Permissible Exposure Limits (PELs) Table Z-1	glycerol	Glycerin (mist)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	glycerol	Glycerin (mist)	Not Available	Not Available	Not Available	See Appendix D

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
propylene glycol	30 mg/m3	330 mg/m3		2,000 mg/m3
propylene glycol	30 mg/m3	1,300 mg/m3		7,900 mg/m3
glycerol	45 mg/m3	180 mg/m3		1,100 mg/m3
Ingredient	Original IDLH		Revised IDLH	
propylene glycol	Not Available		Not Available	
glycerol	Not Available	Not Available		
water	Not Available		Not Available	

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating Occupational Exposure Band Limit		
propylene glycol	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

MATERIAL DATA

for propylene glycol:

Saturated vapour concentration @ 20 deg C.= 65.8 ppm, 204.6 mg/m3; i.e higher concentrations can only occur as aerosols or at higher temperatures. Odour Threshold: Practically odourless.

A small number of individuals show skin irritation or sensitisation from repeated or prolonged exposure to propylene glycol. A workplace environmental exposure limit (WEEL) has been established by AIHA and is thought to be protective against systemic effects.

Exposure controls

Body protection	The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. See Other protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Skin protection	See Hand protection below
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Personal protection	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

	▶ Overalls.
	► PVC Apron.
	PVC protective suit may be required if exposure severe.
	▶ Eyewash unit.
Other protection	Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may
	produce static electricity.
	For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
	• Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole
	made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground
	the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

FW-BSF N&A Bananas Foster Flavor

Material	CPI
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NITRILE	С
PE	С
PE/EVAL/PE	С
PVA	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 Physical and chemical properties

Appearance Brown

Information on basic physical and chemical properties

Appearance	BIOWII		
Physical state	Liquid	Relative density (Water= 1)	1.08
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	51.5	Taste	Bananas foster

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence. In the absence of such evidence, care should be taken nevertheless to ensure exposure is kept to a minimum and that suitable control measures be used, in an occupational setting to control vapours, fumes and aerosols. Inhalation hazard is increased at higher temperatures. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.
Ingestion	Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. Excessive repeated ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible individuals; this may result in muscular weakness, incoordination and mental confusion. Very high doses given during feeding studies to rats and dogs produce central nervous system depression (although one-third of that produced by ethanol), haemolysis and insignificant kidney changes. The toxic effects of glycols (dihydric alcohols), following ingestion are similar to those of alcohol, with depression of the central nervous system (CNS), nausea, vomiting and degenerative changes in liver and kidney. Effects on the nervous system characterise over-exposure to higher aliphatic alcohols. These include headache, muscle weakness, glidliness, ataxia, (loss of muscle coordination), confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and diarrhoea. In the absence of effective treatment, respiratory arrest is the most common cause of death in animals acutely poisoned by the higher alcohols. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Accidental ingestion of the material may be damaging to the health of the individual.

Skin Contact	The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. A single prolonged exposure is not likely to result in the material being absorbed in harmful amounts. However the material may be absorbed in potentially harmful amounts when applied in large quantities to severe burns (second or third degree) over large areas of the body as part of a cream, other topical application or by prolonged contact with clothing accidentally wetted by the material. Absorption under such circumstances can elevated serum osmolality and may result in osmotic shock. Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either • produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or • produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there
Eye	Irritation of the eyes may produce a heavy secretion of tears (lachrymation). Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

FW-BSF N&A Bananas	TOXICITY	IRRITATION	
Foster Flavor	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 100 mg - mild	
	Inhalation(Rat) LC50; >44.9 mg/L4h ^[2]	Eye (rabbit): 500 mg/24h - mild	
propylene glycol	Oral(Rat) LD50; >10400 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	
		Skin(human):104 mg/3d Intermit Mod	
		Skin(human):500 mg/7days mild	
		Skin: no adverse effect observed (not irritating) $\!$	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
glycerol	dermal (guinea pig) LD50: 58500 mg/kg ^[1]	Not Available	
	Oral(Rat) LD50; >20<39800 mg/kg ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
water	Oral(Rat) LD50; >90000 mg/kg ^[2]	Not Available	
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 		

PROPYLENE GLYCOL	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.
GLYCEROL	For glycerol: Acute toxicity: Glycerol is of a low order of acute oral and dermal toxicity with LD50 values in excess of 4000 mg/kg bw. At very high dose levels, the signs of toxicity include tremor and hyperaemia of the gastro-intestinal -tract. Skin and eye irritation studies

	indicate that glycerol has low potential to irritate the skin and the eye. The available human and animal data, together with the very widespread potential for exposure and the absence of case reports of sensitisation, indicate that glycerol is not a skin sensitiser. Repeat dose toxicity: Repeated oral exposure to glycerol does not induce adverse effects other than local irritation of the gastro-intestinal tract.		
WATER	No significant acute toxicological data identified	in literature search.	
FW-BSF N&A Bananas Foster Flavor & GLYCEROL	Asthma-like symptoms may continue for months non-allergenic condition known as reactive airwa levels of highly irritating compound. Key criteria in a non-atopic individual, with abrupt onset of p exposure to the irritant. A reversible airflow patte hyperreactivity on methacholine challenge testin also been included in the criteria for diagnosis of	ays dysfunction syndrome (RADS for the diagnosis of RADS include ersistent asthma-like symptoms v ern, on spirometry, with the prese ig and the lack of minimal lympho	which can occur following exposure to high e the absence of preceding respiratory disease, vithin minutes to hours of a documented nce of moderate to severe bronchial
FW-BSF N&A Bananas Foster Flavor & PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low, and large quantities are required to cause perceptible health damage in humans. Serious toxicity generally occurs only at plasma concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time. It would be nearly impossible to reach toxic levels by consuming foods or supplements, which contain at most 1 g/kg of PG. Cases of propylene glycol poisoning are usually related to either inappropriate intravenous administration or accidental ingestion of large quantities by children. The potential for long-term oral toxicity is also low.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	¥	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	~
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×

```
< – Data available to make classification
```

SECTION 12 Ecological information

Toxicity

ot vailable ndpoint C50	Not Available Test Duration (hr)	Not Available	Not Available	Not Available
•	Test Duration (hr)	Creation .		
C50		Species	Value	Sourc
	48h	Crustacea	>0.342mg/L	4
C50	96h	Fish	>10000mg/l	2
C50	96h	Algae or other aquatic plants	19000mg/l	2
OEC(ECx)	336h	Algae or other aquatic plants	<5300mg/l	1
C50	72h	Algae or other aquatic plants	19300mg/l	2
ndpoint	Test Duration (hr)	Species	Value	Sourc
C0(ECx)	24h	Crustacea	>500mg/l	1
C50	96h	Fish	885mg/l	2
ndpoint	Test Duration (hr)	Species	Value	Source
ot vailable	Not Available	Not Available	Not Available	Not Availab
	DEC(ECx) C50 ndpoint C0(ECx) C50 C50 ndpoint ot vailable	DEC(ECx) 336h C50 72h Test Duration (hr) C0(ECx) 24h C50 96h Test Duration (hr) Not Available	DEC(ECx) 336h Algae or other aquatic plants C50 72h Algae or other aquatic plants Image: color co	DEC(ECx) 336h Algae or other aquatic plants <5300mg/l C50 72h Algae or other aquatic plants 19300mg/l Indpoint Test Duration (hr) Species Value C0(ECx) 24h Crustacea >500mg/l C50 96h Fish 885mg/l Indpoint Test Duration (hr) Species Value Not Available Not Not

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol.

Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms.

Vendor Data

For glycerol log Kow : -2.66 - -2.47 BOD 5: 0.617-0.87,31-51% COD : 1.16,82-95% ThOD : 1.217-1.56 Completely biodegradable. Environmental fate: Based on the relevant physical-chemical properties and the fact that glycerol is readily biodegradable, glycerol will partition primarily to water. Biodegradability: Glycerol is considered to be readily biodegradable in the aquatic environment. Pre-adapted microorganisms can degrade glycerol rapidly under both aerobic and anaerobic conditions. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
glycerol	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
propylene glycol	LOW (BCF = 1)	
glycerol	LOW (LogKOW = -1.76)	

Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
glycerol	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods	6
Product / Packaging disposal	 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO

Land transport (DOT)

UN number	1197	1197		
UN proper shipping name	Extracts, flavori	g, liquid		
Transport hazard class(es)	Class 3 Subrisk No	Applicable		
Packing group	Ш	III		
Environmental hazard	Not Applicable	Not Applicable		
Special precautions for user	Hazard Label	3 ons B1, IB3, T2, TP1		

Air transport (ICAO-IATA / DGR)

UN number	1197			
UN proper shipping name	Extracts, flavouring, liquid			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	3 Not Applicable 3L		
Packing group	Ш	III		
Environmental hazard	Not Applicable			
Special precautions for user		Qty / Pack Packing Instructions	A3 366 220 L 355 60 L Y344 10 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1197			
UN proper shipping name	EXTRACTS, FLAVO	URING, LIQUID		
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk Not Applicable			
Packing group	Ш	III		
Environmental hazard	Not Applicable			
Special precautions for user	EMS NumberF-E, S-DSpecial provisions223 955			
	Limited Quantities	5 L		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

propylene glycol Not Available	
glycerol Not Available	
water Not Available	

Transport in bulk in accordance with the ICG Code

Product name	Ship Type

Product name

Ship Type

FW-BSF N&A Bananas Foster Flavor

	Not Available		
propylene glycol glycerol	Not Available Not Available		
	Not Available		
water	Not Available		
ECTION 15 Regula	tory information		
afety health and e	nvironmental regulations / legislation spe	cific for the substance or mixture	
arety, nearth and er	initioninental regulations / registration spec		
propylene glycol is fou	nd on the following regulatory lists		
	Levels for Hazardous Substances (MRLs)	US Toxic Substances Control Act (TSCA) - Chemical	-
	ergency Exposure Limits (TEELs)	US Toxicology Excellence for Risk Assessment (TER Environmental Exposure Levels (WEEL)	(A) Workplace
US EPA Integrated Risk	Information System (IRIS)	US TSCA Chemical Substance Inventory - Interim Lis	st of Active Substances
glycerol is found on th	e following regulatory lists		
	ergency Exposure Limits (TEELs)	US Toxic Substances Control Act (TSCA) - Chemical	-
	ed Exposure Limits (RELs)	US TSCA Chemical Substance Inventory - Interim Lis	st of Active Substances
US USHA Permissible E	xposure Limits (PELs) Table Z-1		
water is found on the fe	ollowing regulatory lists		
US Toxic Substances Co	ontrol Act (TSCA) - Chemical Substance Inventory	US TSCA Chemical Substance Inventory - Interim Lis	st of Active Substances
ederal Regulations			
Superfund Amendm	ents and Reauthorization Act of 1986 (SA	RA)	
-	-	RA)	
Section 311/312 hazard	l categories	RA)	Yes
Section 311/312 hazard	l categories	RA)	Yes No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure	l categories	RA)	
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive	l categories	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating	l categories osols, Liquids, or Solids)	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So	l categories osols, Liquids, or Solids)	RA)	No No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas	l categories osols, Liquids, or Solids)	RA)	No No No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal	l categories osols, Liquids, or Solids) lid)	RA)	No No No No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or	l categories osols, Liquids, or Solids) lid)	RA)	No No No No No No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide	l categories osols, Liquids, or Solids) lid)	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive	l categories psols, Liquids, or Solids) lid)	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em	l categories psols, Liquids, or Solids) lid)	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust	l categories psols, Liquids, or Solids) lid)	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity	I categories psols, Liquids, or Solids) lid) · Gas) its flammable gas	RA)	No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route	I categories psols, Liquids, or Solids) lid) · Gas) its flammable gas	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity	I categories psols, Liquids, or Solids) lid) · Gas) its flammable gas of exposure)	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritatio	l categories psols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) pn	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens	I categories bosols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens Serious eye damage or othered	l categories psols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization eye irritation	RA)	No Yes No Yes
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens Serious eye damage or of Specific target organ tox	I categories bosols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization	RA)	No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens Serious eye damage or othered	l categories psols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization eye irritation	RA)	No Yes No Yes
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens Serious eye damage or of Specific target organ tox	l categories psols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization eye irritation	RA)	No Yes No No
Section 311/312 hazard Flammable (Gases, Aero Gas under pressure Explosive Self-heating Pyrophoric (Liquid or So Pyrophoric Gas Corrosive to metal Oxidizer (Liquid, Solid or Organic Peroxide Self-reactive In contact with water em Combustible Dust Carcinogenicity Acute toxicity (any route Reproductive toxicity Skin Corrosion or Irritation Respiratory or Skin Sens Serious eye damage or of Specific target organ tox Aspiration Hazard	l categories psols, Liquids, or Solids) lid) Gas) its flammable gas of exposure) on sitization eye irritation	RA)	No Yes No Yes No No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

None Reported

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (propylene glycol; glycerol; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	04/30/2021
Initial Date	05/01/2021

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.